

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/113026 A1

(51) International Patent Classification⁷: **B25B 13/48**,
13/50

(21) International Application Number:
PCT/IL2004/000555

(22) International Filing Date: 22 June 2004 (22.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
156633 25 June 2003 (25.06.2003) IL

(71) Applicant and

(72) Inventor: MEKLER, Dan [IL/IL]; 6 Israel Eldad Street,
93399 Jerusalem (IL).

(74) Agent: FREIMANN, Daniel; Daniel Freimann & Co., 5
Droyanov Street, 63143 Tel-Aviv (IL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: A FASTENING TOOL FOR SCREW THREADED BOLTS



(57) Abstract: Provided according to the invention is a fasten-
ing tool (10) for tightening/untightening screw threaded fasteners
such as bolts or nuts (18). The bolts (18) comprise a head formed
with a series of at least three cavities (18a) deployed therearound.
The fastening tool (10) comprises at least three peanut-shaped dis-
placeable locking bodies (16) having spherical portion (16a; 16b),
and a restricted neck portion (16c) therebetween. The cavities
(18a) of the bolt (18) are configured to receive the spherical por-
tions (16b). A seat member (12) is provided, formed with a series
of at least three cavities (22) configured to receive the spherical
portions (16a). Further provided is a manipulator (14) for rock-
ing the locking bodies (16) about their neck portions (16c) from a
non-operative position wherein the spherical portions (16a) are
seated in the cavities (22), into an operative position wherein the
spherical portions (16b) are seated in the bolt cavities (18a), and
vice versa.

WO 2004/113026 A1